



ENREJADOS AGRÍCOLAS, GANADEROS Y CINEGÉTICOS

**ANUDADO "A" - TRIPLE GALVANIZADO**

Fabricación con alambre galvanizado reforzado (210/240 gr. Zn/m<sup>2</sup>).

Conforme a Norma DIN-177 (Espesores, longitud y peso).

Recubrimiento de acuerdo a Norma EN 10244-2.

Rm. Horiz. 800/900 N/mm<sup>2</sup>. Vert 450 N/mm<sup>2</sup>.

**GAMA ESTÁNDAR**



Tipo	L-mts.	Alambres	Rollos/Palet	Peso	€/Rollo
060 / 06 / 15	50	2,4/1,9/1,9 mm.	23	14,3	39,21
080 / 06 / 15	50	2,4/1,9/1,9 mm.	23	15,8	43,19
080 / 08 / 15	50	2,4/1,9/1,9 mm.	23	18,8	51,33
100 / 08 / 15	50	2,4/1,9/1,9 mm.	23	20,3	51,91
100 / 08 / 30	100	2,4/1,9/1,9 mm.	16	33,8	85,72
100 / 15 / 15	50	2,4/1,9/1,9 mm.	16	31,5	82,98
130 / 18 / 15	50	2,4/1,9/1,9 mm.	16	35,1	104,88
145 / 18 / 15	50	2,4/1,9/1,9 mm.	16	40,0	107,14
200 / 22 / 15	50	2,4/1,9/1,9 mm.	16	45,3	135,35

**GAMA FORESTAL**



Tipo	L-mts.	Alambres FORESTAL ALTA RESISTENCIA 3xZn	Rollos/Palet	Peso	€/Rollo
150 / 13 / 15	50	2,0/1,6/1,6 mm.	23	23,0	66,58
160 / 23 / 15	50	2,0/1,6/1,6 mm.	23	32,0	92,05
180 / 24 / 15	50	2,0/1,6/1,6 mm.	23	34,0	109,23
160 / 15 / 15	50	2,5/2,0/2,0 mm.	16	39,0	111,00
160 / 23 / 15	50	2,5/2,0/2,0 mm.	16	52,0	153,67
200 / 17 / 15	50	2,5/2,0/2,0 mm.	23	45,0	130,14
200 / 17 / 30	50	2,5/2,0/2,0 mm.	23	33,0	97,16